



HIGH VOLTAGE CERAMIC CAPACITOR

CAPACITANCE RANGE / DIMENSION CHART:

TC TYPE (CLASS I)

W.V. (DC)	DIMENSION (mm)			TEMPERATURE CHARACTERISTIC (Capacitance in pF)			
	D	T	d φ	NPO	N750	SL	
500V	6	4	0.5	1 - 36	15 - 36	1 - 150	
	7	4	0.5	39 - 56	39 - 56	180 - 220	
	8	4	0.5	--	--	270 - 330	
	9	4	0.5	68 - 100	68 - 100	390 - 470	
	10	4	0.5	--	--	680	
	11	4	0.5	120 - 150	120 - 150	--	
	12	4	0.5	--	--	820	
	14	4	0.5	--	--	1000	
	1KV	6	5	0.6	--	--	1 - 33
		7	5	0.6	10 - 22	--	47
		8	5	0.6	--	--	56
		9	5	0.6	27 - 62	--	82
		10	5	0.6	--	--	100
		12	5	0.6	68	--	150
14		5	0.6	--	--	220	
16		5	0.6	--	--	330	
18		5	0.6	--	--	470	
2KV		7	6	0.6	4 - 20	--	1 - 33
	8	6	0.6	--	--	39 - 47	
	9	6	0.6	27 - 47	--	56	
	10	6	0.6	--	--	68 - 82	
	12	6	0.6	--	--	100	
	14	6	0.6	--	--	150	
	16	6	0.6	--	--	220	
	18	6	0.6	--	--	330	
	20	6	0.6	--	--	470	