



ALUMINUM ELECTROLYTIC CAPACITOR

TYPE RX

MINIATURE, LOW ESR, HIGH RIPPLE CURRENT, RADIAL LEADS

CASE SIZE (DxL mm) AND PERMISSIBLE RIPPLE CURRENT (mA rms, at 105 120 Hz):

W.V.	6.3V		10V		16V		25V		35V		50V		63V	
μF	DxL	R.C.	DxL	R.C.	DxL	R.C.	DxL	R.C.	DxL	R.C.	DxL	R.C.	DxL	R.C.
1.0											4X7	9	4X7	10
2.2											4X7	11	4X7	13
3.3											4X7	16	4x7	18
4.7											4x7	20	5x7	25
10							4X7	24	4X7	26	5x7	34	5x11	45
									5X7	30	6.3x7	38	6x7	46
22			4X7	30	4X7	35	6.3X7	48	5X11	54	5x11	62	6.3X11	75
					5X7	39			6.3X7	56	6.3x11	67	8x9	81
33	4X7	34	4X7	40	5X7	51	5X11	61	5X11	70	6.3X11	82	6.3X11	99
			5X7	43	6.3X7	55	6.3X7	64	6.3X11	75	8x9	89	8x11	109
47	4X7	43	5X7	55	5X11	69	5X11	80	6.3X11	89	6.3X11	96	8x11	113
	5X7	47	6.3X7	58	6.3X7	71	6.3X11	83	6X9	97	8x11	116	10x12	150
100	5x11	82	5x11	92	6.3X1	113	6.3X11	130	8x11	154	10X16	185	10X16	212
	6.3x7	85	6.3x11	101	18x9	122	8x11	143	10x12	179				
220	6.3X11	137	6.3X11	150	8X11	190	8X11	225	10X16	268	10X20	296	10X21	367
	8X9	148	8X11	177	10X12	230	10X16	250					13X21	457
330	6.3X11	176	10x12	240	8X11	241	10X16	280	10X21	362	10X21	420	13X26	510
	8X11	198			10X16	287					13X21	450		
470	8X11	238	8X11	252	10X16	305	10X16	390	10X21	441	13X26	571	13X25	647
	10X12	275	10X16	330					13X21	545			16X25	807
1000	10X16	375	10X20	575	13x21	630	13X26	760	16X26	962	16X32	1015	16X32	1210
2200	13X25	672	13X25	819	16x26	940	16X26	1080	18X32	1318				